

# Lecture 5

# **Topics Covered**

**Mathematical Modelling**

# Chapter 2 mathematical models of systems

## 2.1 Introduction

### 2.1.1 Why ?

- 1) Easy to discuss the full possible types of the control systems —only in terms of the system's “mathematical characteristics”.
- 2) The basis of analyzing or designing the control systems.

### 2.1.2 What is ?

Mathematical models of systems — the mathematical relationships between the system's variables.

### 2.1.3 How get ?

- 1) theoretical approaches
- 2) experimental approaches
- 3) discrimination learning

# Chapter 2 mathematical models of systems

## 2.1.4 types

- 1) Differential equations
- 2) Transfer function
- 3) Block diagram、 signal flow graph
- 4) State variables


## 2.2 The input-output description of the physical systems — differential equations

The input-output description—description of the mathematical relationship between the output variable and the input variable of physical systems.

### 2.2.1 Examples

# Chapter 2 mathematical models of systems

## Example 2.1: A passive circuit



define: input  $\rightarrow u_r$    output  $\rightarrow u_c$ .  
we have :

$$Ri + L \frac{di}{dt} + u_c = u_r \quad i = C \frac{du_c}{dt}$$


↓

$$LC \frac{d^2 u_c}{dt^2} + RC \frac{du_c}{dt} + u_c = u_r$$

make :  $RC = T_1$     $\frac{L}{R} = T_2 \Rightarrow T_1 T_2 \frac{d^2 u_c}{dt^2} + T_1 \frac{du_c}{dt} + u_c = u_r$

# Chapter 2 mathematical models of systems

## Example 2.2 : A mechanism



*Define: input  $\rightarrow F$ , output  $\rightarrow y$ . We have:*

$$F - ky - f \frac{dy}{dt} = m \frac{d^2y}{dt^2}$$

↓

$$m \frac{d^2y}{dt^2} + f \frac{dy}{dt} + ky = F$$


*If we make :  $\frac{f}{k} = T_1$ ,  $\frac{m}{f} = T_2$*

*we have :  $T_1 T_2 \frac{d^2y}{dt^2} + T_1 \frac{dy}{dt} + y = \frac{1}{k} F$*

*Compare with example 2.1:  $u_c \rightarrow y$ ,  $u_r \rightarrow F$ ---analogous systems*

# Chapter 2 mathematical models of systems

Example 2.4 : A DC motor



Input  $\rightarrow u_a$ , output  $\rightarrow \omega_1$

$$L_a \frac{di_a}{dt} + R_a i_a + E_a = u_a \dots \text{(1)} \quad (4) \rightarrow (2) \rightarrow (1) \text{ and } (3) \rightarrow (1) :$$

$$M = C_m i_a \dots \text{(2)}$$

$$E_a = C_e \omega_1 \dots \text{(3)}$$

$$M - \bar{M} = \bar{J} \frac{d\omega_1}{dt} + \bar{f} \omega_1 \dots \text{(4)}$$

$$\frac{L_a \bar{J}}{C_e C_m} \ddot{\omega}_1 + \left( \frac{L_a \bar{f}}{C_e C_m} + \frac{R_a \bar{J}}{C_e C_m} \right) \dot{\omega}_1 + \left( \frac{R_a \bar{f}}{C_e C_m} + 1 \right) \omega_1 = \frac{1}{C_e} u_a - \frac{L_a}{C_e C_m} \bar{M} - \frac{R_a}{C_e C_m} \bar{M}$$

## Chapter 2 mathematical models of systems

$$\bar{J} = J_1 + \frac{J_2}{i_1^2} + \frac{J_3}{i_1^2 i_2^2} \dots \text{.....equivalent moment of inertia}$$

$$\text{here : } \bar{f} = f_1 + \frac{f_2}{i_1^2} + \frac{f_3}{i_1^2 i_2^2} \dots \text{.....equivalent friction coefficient}$$

$$\bar{M} = \frac{M_f}{i_1 i_2} \dots \text{.....equivalent torque}$$

(can be derived from :  $\omega_1 = i_1 \omega_2 = i_1 i_2 \omega_3$ )

Make:  $T_e = \frac{L_a}{R_a} \dots \text{.....electric - magnetic time - constant}$

$$T_m = \frac{R_a \bar{J}}{C_e C_m} \dots \text{.....mechanical - electric time - constant}$$

$$T_f = \frac{R_a \bar{f}}{C_e C_m} \dots \text{.....friction - electric time - constant}$$

## Chapter 2 mathematical models of systems

the differential equation description of the DC motor is:

$$\begin{aligned} & T_e T_m \ddot{\omega}_1 + (T_e T_f + T_m) \dot{\omega}_1 + (T_f + 1) \omega_1 \\ &= \frac{1}{C_e} u_a - \frac{1}{J} (T_e T_m \dot{\bar{M}} + T_m \bar{M}) \end{aligned}$$

Assume the motor idle:  $M_f = 0$ , and neglect the friction:  $f = 0$ , we have:


$$T_e T_m \frac{d^2 \omega}{dt^2} + T_m \frac{d\omega}{dt} + \omega = \frac{1}{C_e} u_a$$

Compare with example 2.1 and example 2.2:

$u_c \Leftrightarrow y \Leftrightarrow \omega$ ;     $u_r \Leftrightarrow F \Leftrightarrow u_a$  ----Analogous systems

# Chapter 2 mathematical models of systems

Example 2.5 : A DC-Motor control system



*Input  $\rightarrow u_r$ , Output  $\rightarrow \omega$ ; neglect the friction:*

$$u_k = \frac{R_2}{R_1} (u_r - u_f) = k_1 (u_r - u_f) \dots \dots \dots (1)$$

$$u_f = \alpha \omega \dots \dots \dots (2)$$

$$u_a = k_2 u_k \dots \dots \dots (3)$$

$$T_e T_m \frac{d^2 \omega}{dt^2} + T_m \frac{d\omega}{dt} + \omega = \frac{1}{C_e} u_a - \frac{1}{J} (T_e T_m \dot{\bar{M}} + T_m \bar{M}) \dots \dots (4)$$

# Chapter 2 mathematical models of systems

(2) → (1) → (3) → (4) , we have :

$$T_e T_m \frac{d^2 \omega}{dt^2} + T_m \frac{d\omega}{dt} + (1 + k_1 k_2 \alpha \frac{1}{C_e}) \omega = k_1 k_2 \frac{1}{C_e} u_r - \frac{T_m}{J} (T_e \frac{\bullet}{M} + \frac{\bullet}{M})$$

## 2.2.2 steps to obtain the input-output description (differential equation) of control systems

- 1) Identify the output and input variables of the control systems.
- 2) Write the differential equations of each system's component in terms of the physical laws of the components.
  - \* necessary assumption and neglect.
  - \* proper approximation.
- 3) dispel the intermediate(across) variables to get the input-output description which only contains the output and input variables.

# Chapter 2 mathematical models of systems

4) Formalize the input-output equation to be the “standard” form:

Input variable —— on the right of the input-output equation .

Output variable —— on the left of the input-output equation.

Writing the polynomial—according to the falling-power order.

## 2.2.3 General form of the input-output equation of the linear control systems

——A nth-order differential equation:

Suppose: *input*  $\rightarrow r$  , *output*  $\rightarrow y$

$$y^{(n)} + a_1 y^{(n-1)} + a_2 y^{(n-2)} + \dots + a_{n-1} y^{(1)} + a_n y$$

$$= b_0 r^{(m)} + b_1 r^{(m-1)} + b_2 r^{(m-2)} + \dots + b_{m-1} r^{(1)} + b_m r \dots \dots \dots n \geq m$$

# Chapter 2 mathematical models of systems

## 2.4 Transfer function

Another form of the input-output(external) description of control systems, different from the differential equations.

### 2.4.1 definition

Transfer function: *The ratio of the Laplace transform of the output variable to the Laplace transform of the input variable* with all initial condition assumed to be zero and for the linear systems, that is:

# Chapter 2 mathematical models of systems

$$G(s) = \frac{C(s)}{R(s)}$$

C(s) —— Laplace transform of the output variable

R(s) —— Laplace transform of the input variable

G(s) —— transfer function

## Notes:

- \* Only for the linear and stationary(constant parameter) systems.
- \* Zero initial conditions.
- \* Dependent on the configuration and coefficients of the systems, independent on the input and output variables.

### 2.4.2 How to obtain the transfer function of a system

- 1) If the impulse response  $g(t)$  is known

# Chapter 2 mathematical models of systems

We have:  $G(s) = L[g(t)]$

Because:  $G(s) = \frac{C(s)}{R(s)}$ , if  $r(t) = \delta(t) \Rightarrow R(s) = 1$

Then:  $G(s) = C(s) = L[g(t)]$

Example 2.8 :  $g(t) = 5 - 3e^{-2t} \Rightarrow G(s) = \frac{5}{s} - \frac{3}{s+2} = \frac{2(s+5)}{s(s+2)}$

2) If the output response  $c(t)$  and the input  $r(t)$  are known

We have:  $G(s) = \frac{L[c(t)]}{L[r(t)]}$

# Chapter 2 mathematical models of systems

**Example 2.9:**  $r(t) = 1(t) \Rightarrow R(s) = \frac{1}{s}$  ..... *Unit step function*

$$c(t) = 1 - e^{-3t} \Rightarrow C(s) = \frac{1}{s} - \frac{1}{s+3} = \frac{3}{s(s+3)}$$

..... *Unit step response*

**Then:**

$$G(s) = \frac{C(s)}{R(s)} = \frac{3/s(s+3)}{1/s} = \frac{3}{s+3}$$

## 3) If the input-output differential equation is known

- Assume: zero initial conditions;
- Make: Laplace transform of the differential equation;
- Deduce:  $G(s) = C(s)/R(s)$ .

# Chapter 2 mathematical models of systems

Example 2.10:

$$2\overset{\bullet}{c}(t) + 3\overset{\bullet}{c}(t) + 4c(t) = 5\overset{\bullet}{r}(t) + 6r(t)$$

↓

$$2s^2C(s) + 3sC(s) + 4C(s) = 5sR(s) + 6R(s)$$

↓


$$G(s) = \frac{C(s)}{R(s)} = \frac{5s + 6}{2s^2 + 3s + 4}$$

## 4) For a circuit

- \* Transform a circuit into a operator circuit.
- \* Deduce the  $C(s)/R(s)$  in terms of the circuits theory.

# Chapter 2 mathematical models of systems

Example 2.11: For a electric circuit:



$$U_c(s) = \frac{\frac{1}{sC_1} / (R_2 + \frac{1}{sC_2})}{R_1 + \frac{1}{sC_1} / (R_2 + \frac{1}{sC_2})} \cdot U_r(s) \cdot \frac{\frac{1}{sC_2}}{R_2 + \frac{1}{sC_2}}$$


$$= \frac{1}{T_1 T_2 s^2 + (T_1 + T_2 + T_{12})s + 1} \cdot U_r(s)$$

$$G(s) = \frac{U_c(s)}{U_r(s)} = \frac{1}{T_1 T_2 s^2 + (T_1 + T_2 + T_{12})s + 1}$$

$$\text{here : } T_1 = R_1 C_1; \quad T_2 = R_2 C_2; \quad T_{12} = R_1 C_2$$

# Chapter 2 mathematical models of systems

Example 2.12: For a op-amp circuit



$$G(s) = \frac{U_c(s)}{U_r(s)} = -\frac{R_2 + \frac{1}{sC}}{R_1} = -\frac{R_2 Cs + 1}{R_1 Cs}$$

$$= -k\left(1 + \frac{1}{\tau s}\right) \dots \dots \dots \text{PI-Controller}$$


here :  $k = R_2/R_1$  ;  $\tau = R_2 C$  ..... Integral time constant

# Chapter 2 mathematical models of systems

## 5) For a control system

- Write the differential equations of the control system;
- Make Laplace transformation, assume zero initial conditions, transform the differential equations into the relevant algebraic equations;
- Deduce:  $G(s)=C(s)/R(s)$ .

### Example 2.13 the DC-Motor control system in Example 2.5



## Chapter 2 mathematical models of systems

In Example 2.5, we have written down the differential equations as:

$$T_e T_m \frac{d^2 \omega}{dt^2} + T_m \frac{d\omega}{dt} + \omega = \frac{1}{C_e} u_a - \frac{T_m}{J} (T_e \frac{\dot{M}}{M} + \overline{M}) \dots\dots(4)$$

**Make Laplace transformation, we have:**

$$(T_e T_m s^2 + T_m s + 1) \Omega(s) = \frac{1}{C_e} U_a(s) - \frac{T_e T_m s + T_m}{J} \bar{M}(s) \dots \dots (4)$$

**(2)→(1)→(3)→(4), we have:**

## Chapter 2 mathematical models of systems

$$[T_e T_m s^2 + T_m s + (1 + k_1 k_2 \alpha \frac{1}{C_e})] \Omega(s) = k_1 k_2 \frac{1}{C_e} U_r(s) - \frac{T_e T_m s + T_m}{J} \bar{M}(s)$$

$$G(s) = \frac{\Omega(s)}{U_r(s)} = \frac{k_1 k_2 \frac{1}{C_e}}{T_e T_m s^2 + T_m s + (1 + k_1 k_2 \alpha \frac{1}{C_e})}$$

here :  $T_e = \frac{L_a}{R_a}$  ..... electric-magnetic time-constant


$T_m = \frac{R_a J}{C_e C_m}$  ..... mechanical-electric time-constant

# Chapter 2 mathematical models of systems

## 2.6 block diagram models (dynamic)

Portray the control systems by the block diagram models more intuitively than the transfer function or differential equation models

### 2.6.1 Block diagram representation of the control systems



Examples:

# Chapter 2 mathematical models of systems

## **Example 2.14** For the DC motor in Example 2.4


In Example 2.4, we have written down the differential equations as:

**Make Laplace transformation, we have:**


$$M(s) - \bar{M}(s) = \bar{J}s\Omega(s) + \bar{f}\Omega(s) \Rightarrow \Omega(s) = \frac{1}{\bar{J}s + \bar{f}}[M(s) - \bar{M}(s)].....(8)$$

# Chapter 2 mathematical models of systems

Draw block diagram in terms of the equations (5)~(8):




Consider the Motor as a whole:




# Chapter 2 mathematical models of systems

**Example 2.15** The water level control system in Fig 1.8:




# Chapter 2 mathematical models of systems

The block diagram model is:



# Chapter 2 mathematical models of systems

**Example 2.16** The DC motor control system in Fig 1.9



# Chapter 2 mathematical models of systems

The block diagram model is:

